

INDOOR IP CAMERA

Stay in touch with your home, always, wherever you are



DESCRIPTION

This SmartP2P IP Camera combines high definition video camera with wireless and cloud connectivity to bring high definition video of your home whenever you are, on local network or over the Internet, via connected device of your choice (iOS, Android and Windows free apps are available!). As a part of Zipato Smart Monitoring Kit, you can use it to see live and recorded video upon any alarm event, get attached video on alert or always know if your kids are safe. In combination with bundled devices it can be part of virtually limitless automation scenarios you can create by using Zipato Smart Rule Creator.

PRODUCT FEATURES

- Build in WIFI module, 802.11 b/g/n
- Day/Night Surveillance
- Dual Stream, H.264/MJPEG video Compression
- 3.6MM lens, F2.0
- 720p resolution
- Two-way Audio
- Supports ONVIF and RTSP protocol
- SD card socket for recording storage
- Dual Stream, H.264/MJPEG video compression
- Low power consumption
- Motion Detection alarm via E-Mail, FTP and Micro SD
- WPS - One Button Push Secure Wireless Connection

TECHNICAL SPECIFICATION

POWER SUPPLY

- DC 5V, <4W

INTERFACE

- One 10/100Mbps RJ45
- Built in Wi-Fi
- Power interface
- Reset button
- Built-in MicroSD socket
- 8 infrared LEDs, 5m distance

NETWORK

- Wired interface: RJ45 port for 100BASE-TX
- Wireless speed: IEEE802.11b/g/n 150Mbps
- Operating frequency: 2.4 GHz
- Channel: 1~13
- WPS push wireless connection (optional)
- Security: 64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK

IMAGE PERFORMANCE

- Image sensor: 1/4" CMOS sensor
- Display resolution: 1280x720/640x360/320x180
- Lens: f = 3.6 mm, F = 2.0
- View angle: 60 degree
- IR-cut filter

AUDIO

- Two-way audio
- Audio compression: AAC

ENVIRONMENT PARAMATERS

- Operating temperature: -10°C to 50°C

- Storage temperature: -40°C to 70°C
- Operating humidity: 10% to 90%
- Storage humidity: 3% to 90%

SOFTWARE FEATURES

- Protocols & standards: TCP/IP, DHCP, FTP, SMTP, NTP, UPNP, HTTP, UDP/IP, DDNS P2P
- Image compression: H.264/MJPEG
- Maximal frame rate: 30 fps
- Code rate: 256kbps ~ 2048Mbps
- Account permissions: Three Level
- Motion detection: Supports four motion detection, send alarm pictures or video to email/FTP

DIMENSIONS

- IP Camera: 60 x 70 x 130 mm
- Package: 141 x 90 x 177 mm

WEIGHT

- Camera: 89g
- Package: 385g

REGULATION

- EMC 2004/108/EC, R&TTE 1995/5/EC, LVD 2006/95/EC, FCC Part 15

WARRANTY

- 1 year standard

NOTE: SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE