# IP CAMERA

### Stay in touch with your home, always, wherever you are

#### 

This SmartP2P IP Camera combines high definition video camera with wireless and cloud connectivity to bring high definition video of your home whenever you are, on local network or over the Internet, via connected

device of your choice (iOS, Android and Windows free apps are available!). As a part of Zipato Smart Monitoring Kit, you can use it to see live and recorded video upon any alarm event, get attached video on alert or always know if your kids are safe. In combination with bundled devices it can be part of virtually limitless automation scenarios you can create by using Zipato Smart Rule Creator.

#### → PRODUCT FEATURES

- Build in WIFI module, 802.11 b/g/n
- Day/Night Surveillance
- Dual Stream, H.264/MJPEG video Compression
- 3.6MM lens,F2.0
- 720p resolution
- Two-way Audio

- Supports ONVIF and RTSP protocol
- SD card socket for recording storage
- Dual Stream, H.264/MJPEG video compression
- Low power consumption
- Motion Detection alarm via E-Mail, FTP and Micro SD
- WPS One Button Push Secure Wireless Connection

## **TECHNICAL SPECIFICATION**

#### → POWER SUPPLY

DC 5V

#### 

<6W

#### 

Embedded operating system

#### → NETWORK

- TCP/IP, UDP/IP, HTTP, SMTP, FTP, DHCP, DDNS, UPNP, NTP, RTSP, ONVIF
- LAN port; 10Base-T/100Base-TX
- Wi-Fi WiFi 802.11 b/g/n

#### → IMAGE PERFORMANCE

- Resolution: 1280x720, 640x360, 320x180
- Compression mode: H.264/M-JPEG
- Max frame rate: 25fps

#### 

F = 3.6mm, F = 2.0

#### 

CMOS Sensor

#### → MIN. ILLUMINATION

IR on, 0 Lux

#### **⊖** ENVIRONMENT PARAMATERS

- Temperature: -10°C to 50°C (14°F to 122°F)
- Humidity: below 85% RH

#### → ALARM IN/OUT

In support of the 1 road

#### $\bigcirc$ ADDITIONAL FEATURES

- Video control support
- Two-way voice talkback
- Motion detection
- External alarm
- Platform level angle 350 °,100 °vertical angle
- Audio input with microphone
- Audio output
- Support for MS Windows 98/2000/XP/Vista/Windows 7/Mac OS
- Electronic shutter
- SNR
- Safety performance
- Install mode

#### 

- IP Camera: 60 x 40 x 95 mm
- Package: 141 x 90 x 177 mm

#### 

- Camera: 87g
- Package: 337g

#### 

EMC 2004/108/EC, R&TTE 1995/5/EC, LVD 2006/95/EC, FCC Part 15

#### 

1 year standard

NOTE: SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE



