

OUTDOOR IP CAMERA

Keep an eye on large outdoor areas, day and night, wherever you are



→ DESCRIPTION

Zipato Outdoor IP Camera combines high definition recording with wireless and cloud connectivity to bring HD video of large outdoor areas wherever you are, locally or over the Internet, via connected device of your choice. It is IP66 rated, for dust and rain protection. As a part of Zipato Smart Monitoring Kit, you can use it to see live and recorded video upon any alarm event, get attached video on alerts and many more. Joined in Zipato network, it can be part of virtually limitless automation scenarios you can create by using Zipato Rule Creator.

→ PRODUCT FEATURES

- 1.0 Mega Pixel lens, f=3.6mm, F=2.0, 1/4" HD sensor
- Day/Night Surveillance, 20m night vision
- Dual Stream, H.264/MJPEG video Compression
- Supports IEEE 802.11n Wireless Connection
- Supports ONVIF and RTSP protocol
- WEP, WPA and WPA2 encryption
- Waterproof IP66 for outdoor use
- Low power consumption

TECHNICAL SPECIFICATION

→ POWER SUPPLY

- DC 12V, <8W

→ INTERFACE

- One 10/100Mbps RJ45
- Wi-Fi optional
- Power Interface
- Reset Button
- Built-in 8GB MicroSD
- 24 infrared LEDs, 20m distance

→ PAN/TILT

- N/A

→ IMAGE PERFORMANCE

- Image sensor: 1/4" CMOS Sensor
- Display resolution: 1280x720/640x360/320x180
- Lens: F=3.6mm, F=2.0
- View angle: 60 degree

→ WIRELESS

- Wireless speed: IEEE802.11b/g/n 150Mbps
- Operating frequency: 2.4 GHz
- Channel: 1-13
- Security: 64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK
- WPS push wireless connection(optional)

→ SOFTWARE FEATURES

- Account permissions: Three level
- Protocols & Standards: TCP/IP, DHCP, FTP, SMTP, NTP, UPNP, HTTP, UDP/IP, DDNS P2P
- Image compression: H.264/MJPEG
- Maximal frame rate: 30fps

- Code rate: 256kbps ~ 2048Mbps
- Image settings: saturation, brightness, contrast adjustable through client software or web browser
- Motion detection: supports four motion detection, send alarm pictures or video to email/FTP/MicroSD

→ AUDIO

- N/A

→ ENVIRONMENT PARAMETERS

- Operating temperature: -10°C to 50°C
- Storage temperature: -40°C to 70°C
- Operating humidity: 10% to 90%
- Storage humidity: 3 % to 90%
- Waterproof: IP66

→ DIMENSIONS

- IP Camera: 200 x 70 x 65 mm
- Package: 230 x 150 x 100 mm

→ WEIGHT

- Camera: 280g
- Package: 542g

→ REGULATION

- EMC 2004/108/EC, R&TTE 1995/5/EC, LVD 2006/95/EC, FCC Part 15

→ WARRANTY

- 1 year standard

NOTE: SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE