

# INDOOR DOME IP CAMERA



Stay in touch with your home, always, wherever you are

## DESCRIPTION

Zipato Indoor dome IP Camera combines high definition video recording with wireless and cloud connectivity to bring HD video of your home whenever you are, on local network or over the Internet, via connected device of your choice (iOS, Android and Windows free apps are available). Dome like shape makes it difficult for intruder to tell which direction the lens are aiming and fashionable design allows it to seamlessly blend into any surrounding. As a part of Zipato Smart Monitoring Kit, you can use it to see live and recorded video upon any alarm event and get attached video on alert. Joined in Zipato network, it can be part of virtually limitless automation scenarios you can create by using Zipato Rule Creator.

## PRODUCT FEATURES

- Build in WIFI module, 802.11 b/g/n
- Day/Night Surveillance
- Dual Stream, H.264/MJPEG video Compression
- 1.0 Megapixel lens, f=3.6mm, F=2.0, 1/4" HD sensor
- WPS - One Button Push Secure Wireless Connection
- WEP, WPA and WPA2 Encryption
- Supports ONVIF and RTSP protocol
- SD card socket for recording storage
- Motion detection alarm
- Low power consumption

## TECHNICAL SPECIFICATION

### POWER SUPPLY

- DC 12V, <8W

### INTERFACE

- One 10/100Mbps RJ45
- WI-FI support
- Power interface
- Reset button
- 15 infrared LEDs, 10m distance

### PAN/TILT

- N/A

### IMAGE PERFORMANCE

- Image sensor: 1/4" CMOS Sensor
- Display resolution: 1280x720/640x360/320x180
- Lens: F=3.6MM, F=2.0
- View angle: 60 degree

### WIRELESS

- Wireless speed: IEEE802.11b/g/n 150Mbps
- Operating frequency: 2.4 GHz
- Channel: 1-13
- Security: 64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK
- WPS push wireless connection

### SOFTWARE FEATURES

- Account permissions: Three level
- Protocols & Standards: TCP/IP, DHCP, FTP, SMTP, NTP, UPNP, HTTP, UDP/IP, DDNS, P2P
- Image compression: H.264/MJPEG
- Maximal frame rate: 30fps
- Motion detection: send alarm pictures or video to email/FTP/SD

- Account permissions: Three level
- Code rate: 256kbps ~ 2048Mbps
- Image settings: saturation, brightness, contrast adjustable through client software or web browser

### AUDIO

- N/A

### ENVIRONMENT PARAMETERS

- Operating temperature: -10°C to 50°C
- Storage temperature: -40°C to 70°C
- Operating humidity: 10% to 90%
- Storage humidity: 3 % to 90%
- Waterproof: No

### DIMENSIONS

- IP Camera: 168 x 57 x 57 mm
- Package: 220 x 150 x 130 mm

### WEIGHT

- Camera: 87g
- Package: 337g

### REGULATION

- EMC 2004/108/EC, R&TTE 1995/5/EC, LVD 2006/95/EC, FCC Part 15

### WARRANTY

- 1 year standard

NOTE: SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE