



zipato® ZIPATILE ALL IN ONE

One device = complete home control and automation



SECURITY ALARM

- Motion sensor
- Noise sensor
- Shock sensor
- Touch keypad
- Multi-sound alarm siren
- Photo and video messages
- 24/7 central monitoring
- Remote control with smartphone



HOME AUTOMATION

- Remote control with smartphone
- Online rule creator
- Scene manager
- Room manager
- Z-Wave, ZigBee, Nest, Philips Hue, Sonos, Bluetooth...



ELDERLY CARE

- Motion sensor
- Noise detector
- Automatic check calls
- Panic button with auto call
- Sound reminders
- Video and voice calls



WALL PANEL

- Room temperature
- Room illuminance
- Room humidity
- Weather forecast
- Sticky notes
- News stream
- Photo frame
- Email, Skype, browser
- Multimedia control
- Scene controller with 6 buttons



THERMOSTAT

- Gas/floor heating
- Temperature meter
- Exterior temperature meter
- Air condition control
- Remote control with smartphone



INTERCOM

- SIP server client
- Door phone control
- Conference calls
- Video calls
- Dual-network IP connectivity
- Remote control with smartphone



IP CAMERA

- 2 megapixels
- Live video stream H.264
- Motion and scheduled recordings
- Remote control with smartphone



ZIPATILE

Zipatile is the complete home control system in a form of a single device. It can easily be mounted on any wall, in any home. Featuring large number of built-in sensors and hardware modules, ZipaTile will replace numerous home devices such as security system, thermostat, automatic controller, IP camera, alarm siren or intercom, and bring them together in one, smart and beautiful device.



TECHNICAL SPECIFICATION

→ APPLICATIONS

- Security System
- Thermostat
- Elderly Care System
- Home Automation
- Video Monitoring
- Intercom
- Room Controller

→ SYSTEM

- ARM Cortex-A9, Quad-core 1.6GHz CPU
- 1024MB RAM
- 8192MB FLASH
- Android 5 Lollipop

→ NETWORK

- Wi-Fi 802.11 b/g/n
- Ethernet (with optional adapter)
- Bluetooth 4.0
- Philips Hue
- Sonos
- Nest
- Z-Wave+ (500 series)

→ SENSORS

- Noise
- Light
- Humidity
- Temperature
- Motion
- Shock

→ POWER

- Power input: 5VDC
- Power supply input: 100-240VAC, 50/60Hz
- Power usage: <2W (Idle), 7W (Max.)
- Backup battery: Li-Ion 3.7V 2000mAh

→ INPUT/OUTPUT

- Touch sensitive 8" screen, 800x1280 px
- 6 programmable scene buttons
- Dual dry output 230VAC, 1A

Dry input 12-24VDC

External temperature sensor (1-Wire DS18B20)

2MP video camera

Muti-sound alarm siren

SD card

Speaker 8Ω/0.5W

Microphone

→ ACCESSORIES

- In-Wall power supply
- Wall socket adapter
- Wall holder
- Screws
- Table stand

→ PHYSICAL DIMENSION

8.05(W) x 8.05 (H) x 0.35 (D) inches
205(W) x 205(H) x 5(D) millimeters

→ WEIGHT

494g (17.42oz)

→ ENVIRONMENTAL

Operating temperature: 0°C to 40°C (32°F to 104°F)
Storage temperature: -25°C to 70°C (-13°F to 158°F)
Humidity: 5% to 95% non-condensing

→ REGULATION

Safety: UL power supply
EMC: FCC, CE
RoHS

→ MODELS

zt8.zweu.g
zt8.zweu.gb
zt8.zwus
zt8.zbzweuzb.g

→ WARRANTY

1 year standard