

One device = complete home control and automation



SECURITY ALARM

Motion sensor Noise sensor Shock sensor Touch keypad Multi-sound alarm siren Photo and video messages 24/7 central monitoring Remote control with smartphone



HOME AUTOMATION

Remote control with smartphone Online rule creator Scene manager Room manager Z-Wave, ZigBee, Nest, Philips Hue, Sonos, Bluetooth...



ELDERLY CARE

Motion sensor Noise detector Automatic check calls Panic button with auto call Sound reminders Video and voice calls



WALL PANEL

Room temperature Room illuminance Room humidity Weather forecast Sticky notes News stream Photo frame Email, Skype, browser Multimedia control Scene controller with 6 buttons



THERMOSTAT

Gas/floor heating Temperature meter Exterior temperature meter Air condition control Remote control with smartphone



INTERCOM

SIP server client Door phone control Conference calls Video calls Dual-network IP connectivity Remote control with smartphone



IP CAMERA

2 megapixels Live video stream H.264 Motion and scheduled recordings Remote control with smartphone









ZIPATILE

Zipatile is the complete home control system in a form of a single device. It can easily be mounted on any wall, in any home. Featuring large number of built-in sensors and hardware modules, ZipaTile will replace numerous home devices such as security system, thermostat, automatic controller, IP camera, alarm siren or intercom, and bring them together in one, smart and beautiful device.



TECHNICAL SPECIFICATION

→ APPLICATIONS

Security System
Thermostat
Elderly Care System
Home Automation
Video Monitoring
Intercom
Room Controller

→ SYSTEM

ARM Cortex-A9, Quad-core 1.6GHz CPU 1024MB RAM 8192MB FLASH Android 5 Lollipop

→ NETWORK

Wi-Fi 802.11 b/g/n Ethernet (with optional adapter) Bluetooth 4.0 Philips Hue Sonos Nest Z-Wave+ (500 series) ZigBee HA

→ SENSORS

Noise Light Humidity Temperature Motion Shock

→ POWER

Power input: 5VDC Power supply input: 100-240VAC, 50/60Hz Power usage: <2W (Idle), 7W (Max.) Backup battery: Li-lon 3.7V 2000mAh

Touch sensitive 8" screen, 800x1280 px 6 programmable scene buttons Dry output 230VAC, 1A (EU: 2x; US: 3x) Dry input 12-24VDC (only EU version) External temperature sensor (1-Wire DS18B20) 2MP video camera Muti-sound alarm siren SD card Speaker $8\Omega/1.5W$ Microphone

→ ACCESSORIES

In-Wall power supply Wall socket adapter Wall holder Screws Table stand Quick start guide

PHYSICAL DIMENSION

 $8.05(W) \times 8.05 (H) \times 0.55 (D)$ inches $205(W) \times 205(H) \times 14(D)$ millimeters

→ WEIGHT

Netto: 579g (20.4oz) Brutto: 1,121kg (39.54oz)

→ ENVIRONMENTAL

Operating temperature: 0°C to 40°C (32°F to 104°F) Storage temperature: -25°C to 70°C (-13°F to 158°F) Humidity: 5% to 95% non-condensing

→ REGULATION

Safety: UL power supply CE, FCC, IC ROHS, REACH

→ MODELS

zt.zwauzbee	Black	Australia
zt.zweuzbee.b	Black	United Kingdom
zt.zweuzbee.g	Black	Europe
zt.zwinzbee	Black	India
zt.zwiszbee	Black	Israel
zt.zwruzbee	Black	Russia
zt.zwuszbee	Black	United States
zt.zwauzbee.wht	White	Australia
zt.zweuzbee.b.wht	White	UUnited Kingdom
zt.zweuzbee.g.wht	White	Europe
zt.zwinzbee.wht	White	India
zt.zwiszbee.wht	White	Israel
zt.zwruzbee.wht	White	Russia
zt.zwuszbee.wht	White	United States

→ WARRANTY

1 year standard