

# INDOOR PTZ IP CAMERA



Stay in touch with your home, always, wherever you are

## DESCRIPTION

Zipato PTZ IP Camera combines Full HD video recording with wireless and cloud connectivity to bring detailed video of your home whenever you are, over local network the Internet, via connected device of your choice (iOS, Android and Windows free apps are available). Pan-tilt-zoom mechanism with remote directional and zoom control makes sure that every corner of your room is covered. As a part of Zipato Smart Monitoring Kit, you can use it to see live and recorded video upon any alarm event and get attached video on alert. Additionally, it can be part of virtually limitless automation scenarios you can create by using Zipato Rule Creator.

## PRODUCT FEATURES

- Supports IEEE 802.11n Wireless Connection
- Day/Night Surveillance
- Dual Stream, H.264/MJPEG video Compression
- 1.0 Megapixel lens, f=3.6mm, F=2.0, 1/4" HD Sensor
- Supports ONVIF and RTSP protocol
- Supports Micro SD Card Cycled Recording
- Built-in microphone and speaker
- Motion Detection alarm via E-Mail, FTP and Micro SD

## TECHNICAL SPECIFICATION

### POWER SUPPLY

- DC 5V, <6W

### INTERFACE

- One 10/100Mbps RJ45
- Built-in Wi-Fi
- Power interface
- Reset button
- Built-in MicroSD socket
- Built-in Microphone and speaker
- 12 infrared LED, 8m distance

### IMAGE PERFORMANCE

- Image sensor: 1/4" CMOS sensor
- Display resolution: 1280x720/640x360/320x180
- Lens: f = 3.6 mm, F = 2.0
- View angle: 60 degree
- IR-cut filter
- Pan/Tilt: 350° horizontal, 90° vertical

### NETWORK

- Wireless speed: IEEE802.11b/g/n 150Mbps
- Operating frequency: 2.4 GHz
- Channel: 1~13
- WPS push wireless connection (optional)
- Security: 64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK

### SOFTWARE FEATURES

- Protocols & standards: TCP/IP, DHCP, FTP, SMTP, NTP, UPNP, HTTP, UDP/IP, DDNS P2P
- Image compression: H.264/MJPEG
- Maximal frame rate: 30 fps
- Code rate: 256kbps ~ 2048Mbps
- Account permissions: Three Level
- Motion detection: Supports four motion detection, send alarm pictures or video to email/FT

### AUDIO

- Two-way audio
- Audio Compression standard: AAC

### ENVIRONMENT PARAMATERS

- Operating temperature: -10°C to 50°C
- Storage temperature: -40°C to 70°C
- Operating humidity: 10% to 90%
- Storage humidity: 3% to 90%

### DIMENSIONS

- IP Camera: 106 x 117 x 126 mm
- Package: 220 x 150 x 130 mm

### WEIGHT

- Camera: -
- Package: -

### REGULATION

- EMC 2004/108/EC, R&TTE 1995/5/EC, LVD 2006/95/EC, FCC Part 15

### WARRANTY

- 1 year standard

NOTE: SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE