SMART COMBUSTIBLE GAS SENSOR

Used for detecting combusting gas leakage and preventing danger caused by gas leakage. It also can be used as Z-Wave repealer to extend wireless transmission distance.



TECHNICAL SPECIFICATION

- → PROTOCOL
- Z-Wave
- → WORKING VOLTAGE
- AC100~240V
- **→ AVARAGE CONSUMPTION**
- <1.5 W
- **→ ALARM SOUND**
- 75Db (1m distance)
- **→ ALARM DENSITY**
- 6% LEL + 3% LEL (natural gas)
- **→ WIRELESS DISTANCE**
- <100m (open area)</p>
- → WORKING TEMPERATURE -10°C to 50°C (14°F to 122°F)
- **→ HUMIDITY**
- <95%RH
- → PHYSICAL DIMENSION
- Device: 68 mm x 75 mm x 76 mm

- Package: 84 mm x 72 mm x 87 mm
- → WEIGHT
- Device: 90 g
- Package: 128 g
- **→ REGULATORY COMPLIANCE**
- Safety: UL
- EMC: FCC, CE
- RoHS
- **→ WARRANTY**
- 1 year standard

NOTE: SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE